

**Specifications**

	<b>Units</b>	<b>Min</b>	<b>Max</b>	
Acid value	mgKOH/g		0.2	n
Hydroxyl Peak Area			28	n
Hydroxyl value	mgKOH/g		3	n
Flash point, Open Cup	°C	233		n
Pour point	°C		-48	n
Colour ASTM D1500			1	n
Kin. viscosity at 100°C	mm <sup>2</sup> /s	5.2	5.9	n
Kin. viscosity at 40°C	mm <sup>2</sup> /s	30	34	n
Water, for 1 litre, 5 litre and 0.25 litre cans	mg/kg		250	n
Water, for 208 litre drums and 20 litre pails	mg/kg		55	n

**Typical Characteristics**

	<b>Units</b>	<b>Value</b>
Rel.density at 15°C		0.992
Appearance		Clear pale yellow liquid

For safety data, please refer to CRODA Material Safety Data Sheet

Revision: 1

Date: 21 June 2006

The information in this publication is believed to be accurate and is given in good faith but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation or warranty, express or implied, is made with respect to information or products including without limitation warranties of merchantability or fitness for a particular purpose or non-infringement of any third party patent or other intellectual property rights including without limit copyright, trademark and designs.

ICEMATIC is a trademark of the CRODA International Plc.

Any trademarks identified herein are trademarks of the Croda group of companies.